




Discharge Hoses

PVC LAY-FLAT FLEXIBLE DISCHARGE HOSE. SYNTHETIC REINFORCED PVC, EASY TO ROLL AND STORE, INEXPENSIVE, WEATHER PROOF, RESISTANT TO OILS AND MANY OTHER CHEMICALS. MILDEW RESISTANT.

NUMBER	DESCRIPTION		
15-1163	1 1/2 X 300' DISCHARGE HOSE		
15-1164	2" X 300' DISCHARGE HOSE		
15-1165	2 1/2" X 300' DISCHARGE HOSE		
15-1166	3" X 300' DISCHARGE HOSE		
15-1167	4" X 300' DISCHARGE HOSE		
15-1168	6" X 300' DISCHARGE HOSE		
15-1169	8" X 300' DISCHARGE HOSE		

**COUPLED WITH NPT PIN LUG
COUPLINGS**

15-1170 1 1/2 X 25'

15-1539 1 1/2 X 50'

15-1540 1 1/2 X 100'

15-1171 2" X 25'

15-1541 2" X 50'

15-1542 2" X 100'

15-1881 2 1/2" X 50'

15-1886 2 1/2" X 100'

15-1883 3" X 50'

15-1884 3" X 100'



**DISCHARGE HOSE COUPLED
MALE X FEMALE**

ALSO AVAILABLE WITH CAM &
GROOVE FITTINGS

Red PVC HD Lay Flat Discharge Hose

RED PVC with spiral synthetic yarn, one layer longitudinal synthetic yarn

General Applications


Rated at 150 PSI the hose is designed for heavy duty discharge applications in mining, construction, industry, agriculture, and marine service. - Limited oil and chemical applications

TEMPERATURE RANGE:

-10F TO +150F

STANDARD LENGTHS:

1-1/2" thru 6" 300 feet

NUMBER	DESCRIPTION	
15-2163	1 1/2"	
15-2164	2"	
15-2165	2 1/2"	
15-2166	3"	
15-2167	4"	
15-2168	6"	