



Quick Disconnect Couplings

HIGH PRESSURE QUICK DISCONNECT ST COUPLINGS ARE RECOMMENDED FOR SERVICE WITH HYDRAULICS, COMPRESSED AIR, GASES, WATER AND VACUUM. THERE IS NO VALVING IN THE SOCKET OR THE PLUG. THE SOCKETS ARE MADE OF SOLID BRASS AND THE PLUGS ARE PLATED STEEL. THE COUPLINGS COME EITHER MALE OR FEMALE THREAD. EXCELLENT FOR PRESSURE WASHER SERVICE.

NUMBER	DESCRIPTION	
14-1795	3/8" QUICK DISCONNECT COUPLER	 A close-up photograph of a brass quick disconnect coupler. It consists of a hexagonal socket with a threaded end and a matching plug with a knurled grip.
14-1796	3/8" QUICK DISCONNECT PLUG AVAIL WITH FEMALE THREADS	 A close-up photograph of a brass quick disconnect plug. It has a hexagonal base and a threaded top section.

14-1797	3/8 MALE STRAIGHT THRU PLUG	
14-1110	1/4" HIGH PRESSURE VALVED FEMALE PLUG	
14-1111	1/4" HIGH PRESSURE VALVED FEMALE COUPLER	
07-1786	GHT QUICK DISC COUPLER	
07-1787	GHT QUICK DISC COUPLER	
43-4002	3/8 FNPT KARCHER ADAPTER	
43-4003	3/8 MNPT KARCHER ADAPTER	
14-1100	1/4 3 POSITION NOZZLE ADAPTER	

All prices are in USD. Copyright 2016 ARONSON Manufacturing .7640 Gloria Ave Van Nuys CA 91406 (818)-787-5160